

auto electrical parts


Technical Information Sheet


Part No. 0-023-00


Quick Release Battery Terminals - offering a practical solution to ordinary battery terminals by means of a quick release clamp mechanism to easily attach or detach the terminals from a vehicle battery.



Technical Drawing (not to scale)







Specification

| Туре | Quick Release Battery Terminals |
|---------------------------------|---------------------------------------|
| Material | Natural Brass |
| Resistance Class | 4.8 |
| Tensile Strength for Traction | 400N/mm2 |
| Limit of Elasticity | 320N/mm2 |
| Minimum Elongation | 14% |
| Electrical Conductivity | 21% |
| Cover Material | Riblene MR30 Low Density Polyethylene |
| Density | (D1505) 0.924 G/CM3 |
| Flammability Rating of Material | UL94 V-2 |
| Max Amperage | 1000Ah |
| Operating temperature | -40°C to +105°C |
| Max Cable Size | 50mm2 |
| Dimensions | See above |
| Approvals | UNI EN 1982:2000 |

The information contained in this document is correct to the best of our knowledge at the time of printing. However, specifications may change at any time without notice.

Tel: +44 (0)1255 555200 Fax: +44 (0)1255 555222 E-mail: sales@durite.co.uk Web: www.durite.co.uk