


auto electrical parts

Technical Information Sheet

Part No. 0-325-07/10/13/19/32/38

Black expandable braided sleeving, flame retardent.
Operating temperature -40°C to 125°C.



Additional information

	I.D (mm)	min I.D.(mm)	max I.D. (mm)
0-325-07	6.4	3.2	9.5
0-325-10	9.5	4.8	15.9
0-325-13	12.7	6.4	19.0
0-325-19	19.1	12.7	31.7
0-325-32	31.8	19.0	38.1
0-325-38	38.1	25.4	57.1

Technical Drawing (not to scale)

Intentionally Blank

Specification

Type	Expandable braided sleeving
Material	PET monofilament yarn
Colour	Black
Expansion ratio	~3:1 (small diameter) to 2:1 (large diameter)
Elongation	20%
Operating temperature	-40°C to +125°C
Melt temperature	250°C
Approvals	UL E304566

The information contained in this document is correct to the best of our knowledge at the time of printing. However, specifications may change at any time without notice.

Gordon Equipments Limited

Durite Works
Valley Road
Dovercourt
Essex CO12 4RX
England

Tel: +44 (0)1255 555200
Fax: +44 (0)1255 555222
E-mail: sales@durite.co.uk
Web: www.durite.co.uk



Registered in England at address shown No. 373113
The words 'Gordon', 'Durite', 'Nolten' and 'Acfil' are registered trade marks